AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (previously amended) A method of recognising a pattern comprising a sequence of sub-patterns, the method comprising:

generating a data sequence representative of a physical entity;

applying the data sequence to a set comprising active models in a network of models including at least one model;

selecting a subset of the outputs of the members of said set according to a predetermined criterion;

adding further models to said set in dependence on the members of said subset, wherein each model represents a sub-pattern and in use outputs an indication of the degree of matching between an input data sub-sequence and the represented sub-pattern, and the further models take at least one of the subset members as inputs, and each model comprises a finite state network; and

assessing each state of members of said set and deactivating those states that do not meet a predetermined criterion, between the applications of successive data sequence elements.

2. (original) A method according to claim 1, wherein a further model is only added to said set if the set does not already contain that model.

3. (previously amended) A method according to claim 1, wherein the data sequence is applied to the network element-by-element and the selection of a subset of the outputs of the set of models is performed for each of successive applications of data sequence elements.

4.-5. (canceled)

- 6. (previously amended) A method according to claim 1, wherein a model is removed from said set if all of its states have been deactivated.
- 7. (previously amended) A method according to claim 1, wherein the criterion applied to the model outputs is harsher than the criterion applied to states within models.
- 8. (previously amended) A method according to claim 1, wherein the application of the criterion applied to model outputs comprises creating a histogram of model outputs on the basis of their values and selecting those outputs in the bins of the histogram which contain the outputs having the best m values, wherein m is an integer.
- 9. (previously amended) A method according to claim 8, wherein model outputs are selected by setting output(s) that are not selected to a predetermined value.

- 10. (previously amended) A method according to claim 1, wherein the application of the criterion applied to all model states comprises creating a histogram of states on the basis of their values and selecting those states in the bins of the histogram which contain the states having the best n values, where n is an integer, for deactivation.
- 11. (previously amended) A method according to claim 1, wherein the pattern to be recognized is a speech pattern.
- 12. (previously amended) A method according to claim 11, wherein the models comprise models of sub-word vocalisations.
- 13. (previously amended) A method of generating a speech signal comprising performing a method according to claim 11, and operating a speech synthesizer in dependence on the result of performance of said method.
- 14. (previously amended) A method of operating a telephone switching centre comprising performing a method according to claim 11 and commanding a telephone switching centre for the purpose of establishing a telephone connection in dependence on the result of the performance of said method.

15. (previously amended) A method of operating a computer so as to recognise a pattern comprising a sequence of sub-patterns, the method comprising: generating a data sequence representative of a physical entity;

applying the data sequence to a set comprising active models in a network of models including at least one model;

selecting a subset of the outputs of the members of said set according to a predetermined criterion; and

adding further models to said set in dependence on the members of said subset, wherein each model represents a sub-pattern and in use outputs an indication of the degree of matching between an input data sub-sequence and the represented sub-pattern, and the further models take at least one of the subset members as inputs, and each model comprises a finite state network; and

assessing each state of members of said set and deactivating those states that do not meet a predetermined criterion, between the applications of successive data sequence elements.

16. (previously amended) A pattern recognition apparatus for recognising a pattern comprising a sequence of sub-patterns, the apparatus comprising:

means for generating a data sequence representative of a physical entity;

means for applying the data sequence to a set comprising active models in a network of models including at least one model;

means for selecting a subset of the outputs of the members of said set according to a predetermined criterion; and

means for adding further models to said set in dependence on the members of said subset, wherein each model represents a sub-pattern and in use outputs an indication of the degree of matching between an input data sub-sequence and the represented sub-pattern, and the further models take at least one of the subset members as inputs, and each model comprises a finite state network; and

means for assessing each state of members of said set and deactivating those states that do not meet a predetermined criterion, between the applications of successive data sequence elements.

- 17. (original) An apparatus according to claim 16, wherein a further model is only added to said set if the set does not already contain that model.
- 18. (previously amended) An apparatus according to claim 16, wherein the data sequence is applied to the network element-by-element and the selection of a subset of the outputs of the first set of models is performed between the applications of successive data sequence elements.

19.-20. (canceled)

- 21. (previously amended) An apparatus according to claim 16, wherein a model is removed from said set if all of its states have been deactivated.
- 22. (previously amended) An apparatus according to claim 16, wherein the criterion applied to the model outputs is harsher than the criterion applied to states within models.
- 23. (previously amended) An apparatus according to claim 16, wherein the pattern to be recognized is a speech pattern.
- 24. (original) An apparatus according to claim 23, wherein the models comprise models of sub-word vocalisations.
- 25. (previously amended) An apparatus for generating speech signal comprising an apparatus according to claim 23, and a speech synthesizer configured for operation in dependence on the operation of the speech recognition apparatus.
- 26. (currently amended) A telephone network apparatus comprising an apparatus according to claim 23 and a telephone switching centre, wherein the telephone switching centre operates to establish a telephone connection in dependence on the operation of the speech-pattern recognition apparatus.

27.-28. (canceled)